

**CITY OF CHARLOTTE** 

**NEIGHBORHOOD & BUSINESS SERVICES** 

## Invitation to Bid HNS 21-2

NOTE: Contractors are not authorized to visit the property before or after the bid walk, without being accompanied by the City's Rehabilitation Specialist.

### **Documents included in Package:**

- 1) Instruction to Bidders
- 2) Specs by Location/Trade (Scope of Work)
- 3) Subcontractor Certifications (if applicable)
- 4) Floor Plan / Site Drawing (if applicable)

#### **Bid Walk & Bid Opening:**

Project Address:	330 Orchard Trace Lane REHAB ONLY		
Bid Walk: July 9, 2020 at 10:00 am			
Bid Opening: July 16, 2020 at 2:00 pm			
Client Name:	Contact Number:		
Project Manager: Mike Taylor	Contact Number: 704-336-4115		

#### **Bid Walk and Bidding Instructions:**

All bid walks are mandatory.

If you are going to be late the policy is the following:

Contact me BEFORE the start time if you are going to be late. If you are going to be more than 10 minutes late, we will proceed without you and you will not be permitted to bid.

The day of a bid walk the best way to reach me is at Mike Taylor (cell # 980-215-1156).

Bids must be received by the date, time and place specified. All others will be considered non responsive and disqualified.

The Bids will be opened at 600 East Trade St. immediately following the above due date and time.



CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Company Acknowledgement:			
The undersigned, having become thoroughly familiar with the terms, conditions, limitations, and provisions of the housing improvement work to be performed at 330 Orchard Trace Lane #6 to be funded through the City of Charlotte Neighborhood & Business Services, in addition, having fully inspected the site in all particulars, hereby proposes and agrees to fully perform the work within the time stated and in strict accordance with the proposed contract documents including furnishing of any and all labor and materials, and to do all work required to complete said Work in accordance with the advised respective contractual, for the sum of money:  All labor, materials, services and equipment necessary for the completion of the Work shown on the Drawings and in the Specifications:			
Written total	Dollars (\$ )		
Specs Dated: 6/24/20	Number of Pages: 7		
Addenda # 1 Dated:	Number of Pages:		
Addenda # 2 Dated:	Number of Pages:		
Project Schedule: Minimum Start Date	2 -		
Completion Deadline:			
Plana Puint and Cinn			

Pieuse Print una Sign:		
Company Name/Firm:		
Authorized Representative Name:		AMATON 100 100 100 100 100 100 100 100 100 10
Signature:	Date:	



CITY OF CHARLOTTE

**NEIGHBORHOOD & BUSINESS SERVICES** 

### **Requirements For Bidders**

The City awards rehabilitation bids to the lowest responsive and responsible bidder. A responsible bidder for the safe home program is one who:

- 1) Is a licensed general contractor in the State of North Carolina;
- 2) Has an Renovate, Repair & Paint Certification (http://www2.epa.gov/lead/renovation-repair-and-painting-program);
- 3) Is not listed on a local, state or federal debarment list;
- 4) Carries an appropriate amounts of insurance;
- 5) Can provide references verifying the contractor has completed work of a similar scope in a good workmanship like manner or successfully completed prior work for the Safe Home program. Referenced work must have been completed in one year or less from date of this invitation to bid.

A responsive bidder must:

- 1) Submit all requested documentation on time;
- 2) Meet the above requirements for responsibility at the time of bid submittal;
- 3) Have the capacity to meet the required schedule for the project.
- 4) Existing rehab projects contracted by the contractor must be on schedule.

The City reserves the right to waive any minor informalities or irregularities, which do not go to the heart of the bid submittal or prejudice other offers, or to reject, for good and compelling reasons, any or all bid submittals.

Mikel Taylor Rehabilitation Specialist City of Charlotte Neighborhood and Business Services 600 E. Trade St. Charlotte, NC 29202

PH: (704) 336-4115 Fax: (704) 632-8575



CITY OF CHARLOTTE

**NEIGHBORHOOD & BUSINESS SERVICES** 

### **Instructions to Bidders**

### **Explanations to Bidders**

Any explanation desired by a Contractor regarding the meaning or interpretation of the advertisement for bids, drawings, specifications, etc., must be requested in writing to the Rehabilitation Specialist with sufficient time allowed for a reply to each Contractor before the submission of their bids. Any interpretation made will be in the form of an addendum to the invitation for bids, drawings, specifications, etc., and will be furnished to all prospective Contractors. The Contractor must acknowledge any revision to the bid documents in the space provided on the bid form and it must be submitted with their bid package.

#### **Preparation of Bids**

Bids shall be submitted on the forms furnished, or copies thereof, and must be manually signed. If erasures or other changes appear on the forms, the person signing the bids must initial each erasure or change

- The Contractor's Bid Proposal must be properly executed and submitted on the form provided. Bids by Contractors must be received by the Rehabilitation Specialist at the time and place specified on the "Invitation to Bid"
- No bid will be considered unless all individual work items on the Bid Form including any addendums are priced. The sum of all work items must equal to the Total Bid Amount.
- Unless called for, alternate bids will not be considered
- Modification of bids already submitted will be considered if received at the office designated in the invitation for bids by the time set for opening of bids

#### **Submittal of Bids**

- Sealed bids will be submitted to the Safe Home Program Office as directed in the invitation to bid prior to or at the appointed bid opening time
- Bid will be time stamped on the date of delivery
- Each bid must be submitted in a sealed envelope bearing on the outside the name of the Contractor, the name of the project for which the bid is submitted, and the date and time of the bid opening
- All bids submitted must be typed or written in ink and signed by the Contractor's designated representative

G:\SELECTIVE REHAB TEAM\forms\bid forms and documents\Invitation to bid WARREN



**CITY OF CHARLOTTE** 

**NEIGHBORHOOD & BUSINESS SERVICES** 

- Failure to include all forms may result in rejection of a bid
- Required Bid Package Forms:
  - o Scope of Work
  - o Addenda Acknowledgement
  - o Itemized Work Sheet
  - Subcontractor Certifications (if applicable)

NEIGHBORHOOD & BUSINESS SERVICES

http://housing.charlottenc.gov | 600 E. Trade Street | Charlotte, NC

Prepared By:
City of Charlotte Housing & Neighborhood Services
600 E. Trade Street
Charlotte, NC 28202
(704) 336-7600

-				
Proper	rtv I	∪et	alls	3

Address:

330 Orchard Trace Lane #6

Charlotte, NC 28213

Structure Type:

Single Unit

Square Feet:

828

Year Built: Property Value: 1974 36200

Tax Parcel:

08925343

Census Tract:

Property Zone:

Council District 4

#### **Additional Comments**

SOW for Bidding

#### Repairs

**Description** 

Floor

Owner:

Owner Phone: Program(s):

Room

**General Requirements** 

Claudette Watson

X - Emergency Repair

(704) 596-9836

SHFY2020

Response Due: 6/24/2020 11:45

**Exterior** 

#### All Contractor's Project Requirements

The contractor is responsible for all project requirements, including but not limited to:

All activities required by the City's COVID-19 Precautions for Residential Housing Rehabilitation Activities policy.

Obtaining all permits required. Said permits shall include all items in this scope of work.

Provide temporary toilet facilities from job start until the completion of work.

Collect construction debris using dust control methods. Contractor shall haul debris away daily using dump trailers or trucks.

Bid Cost: X = Guantity Total Cost

6/24/2020

#### Removal of Asbestos Containing Material

**General Requirements** 

The joint compound on the walls and ceilings is an asbestos containing material (ACM).

The contractor is responsible for the proper removal and disposal of all ACM disturbed in the course of working on this project.

If all disturbed ACM materials will fit into one asbestos waste or glove bag, contractor's workers who are properly trained under OSHA Construction Standard Asbestos Regulations 29 CFR 1926.1101 may remove and dispose of the ACM using safe work practices.

If all disturbed ACM materials will not fit into one asbestos waste or glove bag, or if workers are not properly trained, the contractor shall hire a state certified asbestos abatement firm to remove and dispose of the disturbed ACM materials.

		Base	Quantity	Total Cost
Exterminate Insects			General Re	equirements
Provide owner with a one year service contract with a properly l	icensed extermi	nator.		
Service shall include initial treatment for all observed insect infecontract.	stations with qu	arterly follow up	o treatments ove	er the course of the
Contract shall also provide for callback treatments between sch	eduled treatmer	nts if an infestat	ion re-appears.	
NOTE: Contractor shall inform exterminator that automatic con the express, informed consent of the home owner.	tract renewals a	re not permitte	d. Contracts ma	ny only be renewed with
	Bid Cost:	x_		1
		Base	Quantity	Total Cost
Vinyl Window			General Re	equirements
Remove and properly dispose of existing window units.				
Field measure, order and install new Energy Star rated vinyl, do	ouble glazed LO	W- E slider win	dows with scree	ens.
Repair all areas disturbed by removal and installation.				
Window frames shall be brown vinyl to blend with brickwork per	HOA requireme	ents.		
	Bid Cost:	X		
		Base	Quantity	Total Cost

#### Water Heater 40 Gallon Electric

#### **Building Systems**

Install a 40 gallon, glass lined, high recovery insulated to R-7, double element, electric water heater with 6 year warranty.

Include pressure and temperature relief valve, expansion tank, discharge tube to the top of the catch pan or to outside of structure, shut-off valve and electric supply.

If it is located on an upper floor or if there is no floor drain, install a catch pan drained to the exterior.

Dispose of old water heater appropriately.

	Bid Cost:	х	=	
		Base	Quantity	Total Cost
Replace Electric Panel			General Re	quirements
Replace electrical panel with new 110/220 volt, 150 amp panel	with main disc	onnect and 12	circuit panel board	<b>1.</b>
Label outlets per Code requirements.				
All equipment, materials, and work shall comply with all require	ments of the E	ectrical Code.		
	Bid Cost:	x		
		Base	Quantity	Total Cost
Smoke Detector Hard Wired			Building Sy	vstems
Install UL approved ceiling mounted smoke and heat detectors bedrooms and outside of all sleeping areas.	permanently h	ard wired into o	outlet boxes with b	attery backups in all
Detector in the hall way shall be a combination CO/smoke dete	ector.			
Detector in the hall way shall be a combination CO/smoke detectors shall be interconnected so that when any one detectors.		all other detecto	ors also go off.	
·	ector goes off,	all other detecto	ors also go off.	
All detectors shall be interconnected so that when any one dete	ector goes off,	all other detecto	ors also go off.	
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Comply with all requirements of	ector goes off,		ors also go off. =	
All detectors shall be interconnected so that when any one detection shall comply with all requirements of the Electrical Complyments.	ector goes off, a			Total Cost
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Comply with all requirements of	ector goes off, a	_x	=	Total Cost
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Comparing the Repair all tear out.	ector goes off, a	X Base	= Quantity Kitchen	
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Control Repair all tear out.  Install GFCI for Counter Top Outlets  Provide GFCI protection at kitchen counter top outlets by replace	ector goes off, and code.  Bid Cost:	X Base ceptacles with	= Quantity Kitchen	
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Control Repair all tear out.  Install GFCI for Counter Top Outlets  Provide GFCI protection at kitchen counter top outlets by replace	ector goes off, a	X Base ceptacles with	= Quantity Kitchen	
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Control Repair all tear out.  Install GFCI for Counter Top Outlets  Provide GFCI protection at kitchen counter top outlets by replace	ector goes off, and code.  Bid Cost:	X Base ceptacles with	= Quantity Kitchen GFCI receptacles =	OR by installing GFCI
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Content all tear out.  Install GFCI for Counter Top Outlets  Provide GFCI protection at kitchen counter top outlets by replace breakers on the counter top circuits.	ector goes off, and code.  Bid Cost: cing existing re	X Base ceptacles with ( X Base	= Quantity Kitchen GFCI receptacles = Quantity Bathroom	OR by installing GFCI  Total Cost
All detectors shall be interconnected so that when any one detection installation shall comply with all requirements of the Electrical Content all tear out.  Install GFCI for Counter Top Outlets  Provide GFCI protection at kitchen counter top outlets by replace breakers on the counter top circuits.  Replace GFCI Receptacle 20 AMP	ector goes off, and code.  Bid Cost: cing existing re	X Base  ceptacles with a X Base  cle in the outlet	Quantity  Kitchen  GFCI receptacles  Quantity  Bathroom  t box with a new of	OR by installing GFCI  Total Cost

#### **Bath Exhaust Fan Replace**

#### Bathroom

Install a switched ceiling mounted Energy Star rated exhaust fan in the ceiling. FAN SHALL BE SWITCHED SEPARATELY FROM LIGHT.

Fan shall be quieter than 2 sones and shall move air at 100 cfm.

Proper installation of metal vent and roof or wall cap/damper assembly is included.

Installation of all necessary wiring for fan and switch is included. Switch shall be flush mounted near the door.

All materials and work shall comply with the Electrical and Mec	hanical Codes.			
Repair all ceiling and wall damage caused by the installation.				
	Bid Cost:	)	<=	AND AND THE STREET, ST
		Base	Quantity	Total Cost
Light Fixture Replace			Bathroom	
Install a switched, UL approved, wall mounted 3 or 4 bulb LED	light fixture with	h shades and	lamps.	
Installation includes all necessary wiring per the NC Electrical C	Code.			
Repair all damage to surface materials caused by installation.				
	Bid Cost:		X=	
		Base	Quantity	Total Cost
Senior Easy Access Shower Package			Bathroom	
Remove existing tub and surround, including valve and drain a	nd dispose of p	roperly.		
to talk to the other formations and because the continue of the original formation of the origin	ahah anasialist	and hama au	nor.	

Install blocking for three grab bars at locations determined by rehab specialist and home owner.

Install a 30" x 60" fiberglass shower pan. Pan must be pre-approved by City rehab specialist.

Install cement tile backer board and a ceramic tile surround. Owner's choice of tile.

Install new drain and mixing valve with all associated plumbing lines.

Mixing valve shall be located in the center of the long wall of the shower to be accessible from a seated position.

Install a diverter valve with a handheld sprayer beside the mixing valve.

Shower head shall be located as normal, Install grab bars at designated locations.

Install tempered glass sliding shower doors.

Provide an approved seat manufactured for use in showers.

All materials and work shall comply with the Construction Specifications and the Plumbing Code.

Bid Cost:	2	X=	
_	Base	Quantity	Total Cost

Paint Bathroom Bathroom

Remove or cover hardware, fixtures, accessories, and other room contents that are not to be painted.

Repair all tear out from other construction activities.

Scrape loose, peeling, cracked and blistered areas. Clean oil, grease, fungus, dirt, and dust from surfaces. Fill holes and cracks. Repair any remaining defects in surfaces as necessary to produce smooth paint ready surfaces.

Prime all materials with a stain killing primer.

NOTE: Very old paint or other site conditions may require the use of a bonding primer to achieve a durable finished product. The contractor is responsible for choosing products and processes that insure a durable finished product.

Top coat with two coats of low VOC acrylic semigloss latex paint.

Surfaces to be painted include all walls, ceiling, trim, and doors.

Replace or uncover hardware, fixtures, accessories, and other room contents.

	Dia Cost:	^		
		Base	Quantity	Total Cost
Sheet Vinyl Flooring			Bathroom	
Install ¼" underlayment, properly nailed and leveled.				
Install full glue down sheet vinyl flooring with a 25 year manufac	turer's warranty	•		
Vinyl must be approved by the Rehab Specialist at the pre-cons from which to choose.	truction meeting	j. Provide ow	ner with a minimu	um of three patterns
Install baseboard as necessary to match the existing and install	quarter round a	round the pe	rimeter of the viny	1.
Install appropriate transition strips where vinyl meets other floor	ing types.			
	Bid Cost:	x		
		Base	Quantity	Total Cost
Vanity/ Counter Top/ Sink			Bathroom	

Dial C - -4.

Remove of old vanity and dispose of properly.

Install a new 24" vanity cabinet complete with marble-lite top with preformed sink.

Install single handle metal faucet with P- trap and drain lines to the wall, pop-up drain plug, supply lines, full port ball type shut-off valves & escutcheon plates.

All materials and workmanship shall meet the requirements of the NC Plumbing Code and the Construction Specifications.

Bid Cost:		X=	
	Base	Quantity	Total Cost

17"	Hei	ght	Commode	Replace
-----	-----	-----	---------	---------

#### Bathroom

Install a 17" height, 2 piece, close coupled, white, vitreous china commode with a maximum water usage per flush of 1.6 gallons. Include plastic or pressed wood white seat, supply pipe, shut-off valve, flap valve and wax seal.

**Total Cost Paint Hall** Hall Remove or cover hardware, fixtures, furniture, accessories, and other room contents that are not to be painted. Repair all tear out from other construction activities. Scrape loose, peeling, cracked and blistered areas. Clean oil, grease, fungus, dirt, and dust from surfaces. Fill holes and cracks. Repair any remaining defects in surfaces as necessary to produce smooth paint ready surfaces. Prime all materials with a stain killing primer. NOTE: Very old paint or other site conditions may require the use of a bonding primer to achieve a durable finished product. The contractor is responsible for choosing products and processes that insure a durable finished product. Top coat with two coats of low VOC acrylic flat latex paint. Use semi-gloss paint in kitchens and bathrooms. Surfaces to be painted include all walls and ceiling. Ceilings shall be painted the owner's choice of ceiling white or the selected wall color. Replace or uncover hardware, fixtures, furniture, accessories, and other room contents. Quantity **General Requirements** Refrigerator--18 CF Frost Free Dispose of old refrigerator. Install a 2 door, Energy Star rated frost free refrigerator with at least 18 cubic feet. New refrigerator is to match existing refrigerator like for like (i.e. volume, style (top and bottom or side by side, or if have existing ice maker, install new refrigerator with ice maker as well). **General Requirements Interior Door Leversets** Replace interior door knob sets with lever handle sets. Install privacy sets at bedrooms and bathrooms. Install passage sets at all other doors. Match existing hardware finish unless home owner chooses otherwise.

Quantity

#### **Exterior Door Hardware**

Signature:

**General Requirements** 

Replace entry hardware with lever handle entry set and single keyed deadbolt.

NOTE: Double keyed deadbolts are not permitted.

All new locksets shall be keyed alike.

Deadbolt keepers shall be installed with long screws that attach securely to framing (new prehung doors equipped with reinforced metal plates on the inside of the jamb are also acceptable in lieu of long screws).